



# M12, female, straight, 8 poles, M12, male, straight, 8 poles, sensor-/actuator cable



| Product data       |                          |
|--------------------|--------------------------|
| Item description   | AL-WAK8-1,5-AL-WAS8/S370 |
| Item-No.           | 8049791                  |
| Length             | 1.5m                     |
| Customs tariff-No. | 85444290                 |
| Step-File          | AL-WAK8_AL-WAS8.stp      |
| EAN                | 4047106177102            |

| Technical data                 | A-side                                         | B-side                                         |
|--------------------------------|------------------------------------------------|------------------------------------------------|
| Connector                      | female, straight, M12                          | male, straight, M12                            |
| Number of pins                 | 8                                              | 8                                              |
| Pin assignment                 | 1 WH, 2 BN, 3 GN, 4 YE, 5 GY, 6 PK, 7 BU, 8 RD | 1 WH, 2 BN, 3 GN, 4 YE, 5 GY, 6 PK, 7 BU, 8 RD |
| Coding of                      | A                                              | A                                              |
| Rated voltage                  | 30V                                            | 30V                                            |
| Current load (at 40°C)         | 2A                                             | 2A                                             |
| Insulation resistance          | $\geq 10^9 \Omega$                             | $\geq 10^9 \Omega$                             |
| Resistance                     | $\leq 5 m\Omega$                               | $\leq 5 m\Omega$                               |
| Ambient temperature product    | -30°C...+90°C                                  | -30°C...+90°C                                  |
| Contact material               | Metal, CuZn, gold-plated                       | Metal, CuZn, gold-plated                       |
| Contact-carrier material       | Plastic, TPU, BK                               | Plastic, TPU, BK                               |
| Grip body material             | Plastic, TPU, BK                               | Plastic, TPU, BK                               |
| Coupling nut material          | Metal, CuZn, nickel-plated                     | Metal, CuZn, nickel-plated                     |
| Sealing (female) material      | FPM/FKM                                        |                                                |
| Standards                      | IEC 61076-2-101                                | IEC 61076-2-101                                |
| Degree of protection (mounted) | IP65, IP67, IP68                               | IP65, IP67, IP68                               |
| Mechanical life-cycle          | >100 mating cycles                             | >100 mating cycles                             |
| Degree of pollution            | 3                                              | 3                                              |

## Cable web

PUR, UL, S370

Flexible, silicone- and halogen-free control line with high mechanical strength. The cable is chemicals, hydrolysis-, and microbes- resistant. The drag-chain application is possible at a bending radius of minimum 10 x d. Due to its weld-field immunity, the cable is very well suited for the flexible application in robotics, machine-tool, and metal-cutting production. The cables meet the UL and CSA (UL10493/20549; cULus) requirements.

|                                |                                                                                                                                                                                                                                                                      |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outer diameter of jacket       | 5.90 mm                                                                                                                                                                                                                                                              |
| Cable-jacket material          | PUR                                                                                                                                                                                                                                                                  |
| Jacket color                   | BK, similar RAL9005                                                                                                                                                                                                                                                  |
| Wire cross-section             | 8 x 0.25 mm <sup>2</sup>                                                                                                                                                                                                                                             |
| Wire insulation material       | PP                                                                                                                                                                                                                                                                   |
| Wire colors                    | WH, BN, GN, YE, GY, PK, BU, RD                                                                                                                                                                                                                                       |
| Wire structure                 | 32 x 0.10 mm                                                                                                                                                                                                                                                         |
| Bending radius (fixed)         | 5 x Ø-cable                                                                                                                                                                                                                                                          |
| Bending radius (repeated)      | 10 x Ø-cable                                                                                                                                                                                                                                                         |
| Temperature range (repeated)   | -30°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (fixed)      | -40°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (drag chain) | -25°C...+60°C                                                                                                                                                                                                                                                        |
| Drag chain-application         | ≥2 Mio. cycles                                                                                                                                                                                                                                                       |
| Halogen-free                   | Yes                                                                                                                                                                                                                                                                  |
| Torsion                        | +/-180°/m, ≥ 0.5 Mio. cycles                                                                                                                                                                                                                                         |
| Rated voltage cable            | ≤300 V                                                                                                                                                                                                                                                               |
| Special features               | flame retardant, halogen free, hydrolysis proof, LABS free, oil resistant, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, drag chain-adapted, welding sparks resistant, seawater resistant, silicone free, torsion resistant, UV resistant |

## Classification

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27279218 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |
| ETIM 5.0   | EC001855 |
| ETIM 6.0   | EC001855 |