


Field-wireable, M12, male, straight, 4 poles, screw-/clamp contact, shielded, 250V 4A




Product data

Item description	WASCS4K
Item-No.	8068909
Customs tariff-No.	85366990
Step-File	WAKCS4K.stp
EAN	4047106155650

Technical data

Connector	male, straight, M12
Number of pins	4
Coding	A
Rated voltage	250V
Current load per pin (at 40°C)	4A
Insulation resistance	$\geq 10^9 \Omega$
Resistance	$\leq 3 m\Omega$
Ambient temperature product	-40°C...+85°C
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, PA, BK
Grip body material	Metal, CuZn
Coupling nut material	Metal, CuZn
Shielding	with shielding
Connecting cross-section	max. 0.75 mm ²
Cable outlet	5...8 mm
Connecting type	Screw-/clamp contact
Standards	IEC 61076-2-101
Degree of protection (mounted)	IP67
Mechanical life-cycle	>100 mating cycles
Degree of pollution	3
Style	straight

Manual



Classification

eCl@ss 6.0	27260702
eCl@ss 7.0	27440102
eCl@ss 8.0	27440102
eCl@ss 9.0	27440102
ETIM 5.0	EC002635
ETIM 6.0	EC002635

Link to product

<https://www.escha.net/en/products/standard/field-wireable-connectors/8068909>