


## Receptacle, M8, female, straight, 5 poles, B-coded, back wall-mounting, print contact, shielded









	<b>→ 11</b> □ CH <b>→</b>
Product data	
Item description	AL-FHM8KSB4.5-P/M10
Item-No.	8073391
Customs tariff-No.	85366990
Packaging unit	10
Step-File	AL-FHM8KSB4.5-P_M10.stp
EAN	4047106168667
Technical data	
Connector	female, straight, M8
Number of pins	5
Coding	В
Rated voltage	30V
Current load per pin (at 40°C)	3A
Ambient temperature product	-30°C+90°C
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, TPU, BK
Receptacle housing material	Metal, CuZn, nickel-plated
Sealing (female) material	FPM/FKM
Shielding	with shielding
Mounting direction	Back wall-mounting (incl. Fixing screw)
Adjustable fixing screw	Yes
Fastening thread	M10x1
Connecting type	Print contact
Standards	IEC 61076-2-104
Degree of protection (mounted)	IP65, IP67, IP68
Mechanical life-cycle	>100 mating cycles
Degree of pollution	3
Style	straight



Classification	
eCl@ss 6.0	27279220
eCl@ss 7.0	27440103
eCl@ss 8.0	27440103
eCl@ss 9.0	27440103
ETIM 5.0	EC002061
ETIM 6.0	EC002061
Link to product	

https://www.escha.net/en/products/standard/receptacles/8073391