

## M8, male, straight, 5 poles, sensor-/actuator cable



### Product data

|                    |                    |
|--------------------|--------------------|
| Item description   | AL-SSP4.5-0,5/S370 |
| Item-No.           | 8082874            |
| Length             | 0.5m               |
| Customs tariff-No. | 85444290           |
| Step-File          | AL-SSP4_5.stp      |
| EAN                | 4047106236977      |

### Technical data

|                                |                              |
|--------------------------------|------------------------------|
| Connector                      | male, straight, M8           |
| Number of pins                 | 5                            |
| Pin assignment                 | 1 BN, 2 WH, 3 BU, 4 BK, 5 GY |
| Rated voltage                  | 30V                          |
| Current load per pin (at 40°C) | 3A                           |
| Insulation resistance          | $\geq 10^9 \Omega$           |
| Resistance                     | $\leq 5 m\Omega$             |
| Ambient temperature product    | -30°C...+90°C                |
| Contact material               | Metal, CuZn, gold-plated     |
| Contact-carrier material       | Plastic, TPU, BK             |
| Grip body material             | Plastic, TPU, BK             |
| Coupling nut material          | Metal, CuZn, nickel-plated   |
| Standards                      | IEC 61076-2-104              |
| Degree of protection (mounted) | IP65, IP67, IP68             |
| Mechanical life-cycle          | >100 mating cycles           |
| Cable end assembly             | open cable end               |
| Degree of pollution            | 3                            |
| Style                          | straight                     |

|                  |                      |
|------------------|----------------------|
| <b>Cable web</b> | <b>PUR, UL, S370</b> |
|------------------|----------------------|

Flexible, silicone- and halogen-free control line with high mechanical strength. The cable is chemicals, hydrolysis-, and microbes- resistant. The drag-chain application is possible at a bending radius of minimum 10 x d. Due to its weld-field immunity, the cable is very well suited for the flexible application in robotics, machine-tool, and metal-cutting production. The cables meet the UL and CSA (UL10493/20549; cULus) requirements.

|                                |  |
|--------------------------------|--|
| Outer diameter of jacket       | 4.70 mm  |
| Cable-jacket material          | PUR  |
| Jacket color                   | BK, similar RAL9005  |
| Wire cross-section             | 5 x 0.25 mm <sup>2</sup>   |
| Wire insulation material       | PP   |
| Wire colors                    | BN, WH, BU, BK, GY   |
| Wire structure                 | 32 x 0.10 mm   |
| Bending radius (fixed)         | 5 x Ø-cable  |
| Bending radius (repeated)      | 10 x Ø-cable   |
| Temperature range (repeated)   | -30°C...+90°C  |
| Temperature range (fixed)      | -40°C...+90°C  |
| Temperature range (drag chain) | -25°C...+60°C  |
| Drag chain-application         | 3 Mio. cycles  |
| Halogen-free                   | Yes  |
| Torsion                        | +/-180°/m, < 1 Mio. cycles   |
| Rated voltage cable            | ≤300 V   |
| Special features               | flame retardant, halogen free, hydrolysis proof, LABS free, oil resistant, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, drag chain-adapted, welding sparks resistant, seawater resistant, silicone free, torsion resistant, UV resistant |

|                       |  |
|-----------------------|--|
| <b>Classification</b> |  |
|-----------------------|--|

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27279218 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |
| ETIM 5.0   | EC001855 |
| ETIM 6.0   | EC001855 |

|                    |  |
|--------------------|--|
| <b>Accessories</b> |  |
|--------------------|--|

|                          |  |
|--------------------------|--|
| <b>Mounting-clip, M8</b> |  |
|--------------------------|--|

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8047658>

|                          |  |
|--------------------------|--|
| <b>Torque-wrench set</b> |  |
|--------------------------|--|

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431>

|                            |  |
|----------------------------|--|
| <b>Marking rings Ø 9mm</b> |  |
|----------------------------|--|

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=809>

|                      |  |
|----------------------|--|
| <b>Screw cap, M8</b> |  |
|----------------------|--|

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8081761>

|                             |  |
|-----------------------------|--|
| <b>Cable Stripping Tool</b> |  |
|-----------------------------|--|

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8066215>

|                             |  |
|-----------------------------|--|
| <b>Cable Stripping Tool</b> |  |
|-----------------------------|--|

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8066216>