


Receptacle, M12, female, straight, 4+PE, back wall-mounting, print contact, stainless steel







Product data



Item description	AL-FHM12EKUA5-P/M16
Item-No.	8084924
Customs tariff-No.	85366990
Packaging unit	10
Step-File	AL-FHM12KUA5-P_M16.stp
EAN	4047106252243
Technical data	
Connector	female, straight, M12
Number of pins	4+PE
Coding	А
Rated voltage	60V
Current load per pin (at 40°C)	4A
Insulation resistance	≥10°Ω
Ambient temperature product	-30°C+90°C
Reflow	2 min. 250 °C
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, PA GF, BK
Receptacle housing material	Stainless steel 1.4404
Sealing (female) material	FPM/FKM
Material of external sealing	NBR
Mounting direction	Back wall-mounting (incl. Fixing screw)
Wrench size of fastening nut	A/F19
Fastening thread	M16x1.5
Connecting type	Print contact
Standards	IEC 61076-2-101
Degree of protection (mounted)	IP65, IP67, IP68
Mechanical life-cycle	>100 mating cycles
Degree of pollution	3
Style	straight



Classification	
eCl@ss 6.0	27279220
eCl@ss 7.0	27440103
eCl@ss 8.0	27440103
eCl@ss 9.0	27440103
ETIM 5.0	EC002061
ETIM 6.0	EC002061
Link to product	

https://www.escha.net/en/products/standard/receptacles/8084924