


## Receptacle, M8, female, angled, 4 poles, back wall-mounting, print contact, shielded









Product data	
Item description	AL-WFHM8KSA4-P/M10
Item-No.	8088511
Customs tariff-No.	85366990
Packaging unit	10
Step-File	AL-WFHM8KSA4-P_M10.stp
EAN	4047106254865
Technical data	
Connector	female, angled, M8
Number of pins	4
Coding	A
Rated voltage	50Vac   60Vdc
Current load per pin (at 40°C)	4A
Ambient temperature product	-30°C+90°C
Contact material	Metal, CuZn, gold-plated
Contact-carrier material	Plastic, TPU, BK
Receptacle housing material	Metal, CuZn, nickel-plated
Sealing (female) material	FPM/FKM
Shielding	with shielding
Mounting direction	Back wall-mounting (incl. Fixing screw)
Adjustable fixing screw	Yes
Fastening thread	M10x1
Connecting type	Print contact
Standards	IEC 61076-2-104
Degree of protection (mounted)	IP65, IP67, IP68
Mechanical life-cycle	>100 mating cycles
Degree of pollution	3
Style	angled



Classification	
eCl@ss 6.0	27279220
eCl@ss 7.0	27440103
eCl@ss 8.0	27440103
eCl@ss 9.0	27440103
ETIM 5.0	EC002061
ETIM 6.0	EC002061
Link to product	

https://www.escha.net/en/products/standard/receptacles/8088511