


M12, male, straight, 3 poles, sensor-/actuator cable









| Product data | |
|---|--|
| Item description | AL-WAS3-3/P01BK |
| Item-No. | 8106034 |
| Length | 3m |
| Customs tariff-No. | 85444290 |
| Step-File | AL-WAS3.stp |
| EAN | 4047106295233 |
| Technical data | |
| Connector | male, straight, M12 |
| Number of pins | 3 |
| Pin assignment | 1 BN, 3 BU, 4 BK |
| Coding | A |
| Rated voltage | 250V |
| Current load per pin (at 40°C) | 4A |
| Insulation resistance | >=10°Ω |
| Resistance | $\leq 5 \text{m}\Omega$ |
| Ambient temperature product | -30°C+90°C |
| Contact material | Metal, CuSn, gold-plated |
| Contact-carrier material | Plastic, TPU, BK |
| Grip body material | Plastic, TPU, BK |
| Coupling nut material | Metal, CuZn, nickel-plated |
| | |
| Standards | IEC 61076-2-101 |
| Standards Degree of protection (mounted) | IEC 61076-2-101 IP65, IP67, IP68 |
| | |
| Degree of protection (mounted) | IP65, IP67, IP68 |
| Degree of protection (mounted) Mechanical life-cycle | IP65, IP67, IP68 >100 mating cycles |



| Cable web | PVC. P01BK. UL |
|-----------|----------------|
| | |

PVC-cable for measurement and control-, and sensor technology. Suitable for applications in dry areas on packaging machines, assembly- and conveyor technology. High flexibility with unstressed movement (conditional drag-chain application possible). Predestined for applications in food- and beverage industry.

| Outer diameter of jacket | 4.60 mm | |
|------------------------------|--|--|
| Cable-jacket material | PVC | |
| Jacket color | BK, similar RAL9005 | |
| Wire cross-section | 3 x 0.34 mm ² | |
| Wire insulation material | PVC | |
| Wire colors | BN, BU, BK | |
| Wire structure | 19 x 0.15 mm | |
| Bending radius (fixed) | 5 x Ø-cable | |
| Bending radius (repeated) | 10 x Ø-cable | |
| Temperature range (repeated) | 0°C+80°C | |
| Temperature range (fixed) | -25°C+80°C | |
| Rated voltage cable | ≤300 V | |
| Special features | good resistance against oils and chemicals, LABS free, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, seawater resistant, UV resistant | |

| Classification | | |
|----------------|----------|--|
| eCl@ss 6.0 | 27279218 | |
| eCl@ss 7.0 | 27279218 | |
| eCl@ss 8.0 | 27279218 | |
| eCl@ss 9.0 | 27060311 | |
| ETIM 5.0 | EC001855 | |
| ETIM 6.0 | EC001855 | |

Accessories

 $Mounting-clip,\ M12\\ https://www.escha.net/en/products/standard/accessories-for-connectivity/8047660$

 $Torque-wrench\ set\\ \ https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431$

Marking rings Ø 9mm

escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=809

Screw cap, M12 https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=811 Cable Stripping Tool https://www.escha.net/en/products/standard/accessories-for-connectivity/8066215

Cable Stripping Tool

oducts/standard/accessories-for-connectivity/8066216