


**M12, female, angled, 3 poles, with LED, sensor-/actuator cable**



**Product data**

|                    |                       |
|--------------------|-----------------------|
| Item description   | AL-WWAK3P2-1,5/S370GY |
| Item-No.           | 8110750               |
| Length             | 1.5m                  |
| Customs tariff-No. | 85444290              |
| Step-File          | AL-WWAK3P2.stp        |
| EAN                | 4047106306472         |

**Technical data**

|                                |                               |
|--------------------------------|-------------------------------|
| Connector                      | female, angled, M12, with LED |
| Number of pins                 | 3                             |
| Pin assignment                 | 1 BN, 3 BU, 4 BK              |
| Coding                         | A                             |
| Rated voltage                  | 30V                           |
| Current load per pin (at 40°C) | 4A                            |
| Insulation resistance          | $\geq 10^9 \Omega$            |
| Resistance                     | $\leq 5 m\Omega$              |
| Ambient temperature product    | -30°C...+90°C                 |
| Circuit logic                  | pnp                           |
| Signal status-indicator        | LED YE                        |
| Operating voltage-indicator    | LED GN                        |
| Contact material               | Metal, CuZn, gold-plated      |
| Contact-carrier material       | Plastic, TPU, BK              |
| Grip body material             | Plastic, TPU, transparent     |
| Coupling nut material          | Metal, CuZn, nickel-plated    |
| Sealing (female) material      | FPM/FKM                       |

|                                |                    |
|--------------------------------|--------------------|
| Standards                      | IEC 61076-2-101    |
| Degree of protection (mounted) | IP65, IP67, IP68   |
| Mechanical life-cycle          | >100 mating cycles |
| Cable end assembly             | open cable end     |
| Degree of pollution            | 3                  |
| Style                          | angled             |

|                  |                        |
|------------------|------------------------|
| <b>Cable web</b> | <b>PUR, UL, S370GY</b> |
|------------------|------------------------|

Flexible, silicone- and halogen-free control line with high mechanical strength. The cable is chemicals, hydrolysis-, and microbes- resistant. The drag-chain application is possible at a bending radius of minimum 10 x d. Due to its weld-field immunity, the cable is very well suited for the flexible application in robotics, machine-tool, and metal-cutting production. The cables meet the UL and CSA (UL10493/20549; cULus) requirements.

|                                |                                                                                                                                                                                                                                                                      |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outer diameter of jacket       | 4.30 mm                                                                                                                                                                                                                                                              |
| Cable-jacket material          | PUR                                                                                                                                                                                                                                                                  |
| Jacket color                   | GY, similar RAL7040                                                                                                                                                                                                                                                  |
| Wire cross-section             | 3 x 0.34 mm <sup>2</sup>                                                                                                                                                                                                                                             |
| Wire insulation material       | PP                                                                                                                                                                                                                                                                   |
| Wire colors                    | BN, BU, BK                                                                                                                                                                                                                                                           |
| Wire structure                 | 42 x 0.10 mm                                                                                                                                                                                                                                                         |
| Bending radius (fixed)         | 5 x Ø-cable                                                                                                                                                                                                                                                          |
| Bending radius (repeated)      | 10 x Ø-cable                                                                                                                                                                                                                                                         |
| Temperature range (repeated)   | -30°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (fixed)      | -40°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (drag chain) | -25°C...+60°C                                                                                                                                                                                                                                                        |
| Drag chain-application         | 5 Mio. cycles                                                                                                                                                                                                                                                        |
| Halogen-free                   | Yes                                                                                                                                                                                                                                                                  |
| Torsion                        | +/-360°/m, ≥ 2 Mio. cycles                                                                                                                                                                                                                                           |
| Rated voltage cable            | ≤300 V                                                                                                                                                                                                                                                               |
| Special features               | flame retardant, halogen free, hydrolysis proof, LABS free, oil resistant, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, drag chain-adapted, welding sparks resistant, seawater resistant, silicone free, torsion resistant, UV resistant |

|                       |          |
|-----------------------|----------|
| <b>Classification</b> |          |
| eCl@ss 6.0            | 27279218 |
| eCl@ss 7.0            | 27279218 |
| eCl@ss 8.0            | 27279218 |
| eCl@ss 9.0            | 27060311 |
| ETIM 5.0              | EC001855 |
| ETIM 6.0              | EC001855 |

|                                                                                                                                                                                                                                                    |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| <b>Accessories</b>                                                                                                                                                                                                                                 |  |
| Mounting-clip, M12<br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity/8047660">https://www.escha.net/en/products/standard/accessories-for-connectivity/8047660</a>                                                |  |
| Torque-wrench set<br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431">https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431</a>                                                 |  |
| Marking rings Ø 9mm<br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&amp;o=3&amp;n=15&amp;f=809">https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&amp;o=3&amp;n=15&amp;f=809</a> |  |
| Screw plug, M12<br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&amp;o=3&amp;n=15&amp;f=812">https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&amp;o=3&amp;n=15&amp;f=812</a>     |  |
| Cable Stripping Tool<br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity/8066215">https://www.escha.net/en/products/standard/accessories-for-connectivity/8066215</a>                                              |  |
| Cable Stripping Tool<br><a href="https://www.escha.net/en/products/standard/accessories-for-connectivity/8066216">https://www.escha.net/en/products/standard/accessories-for-connectivity/8066216</a>                                              |  |