



# M12, male, angled, 4 poles, D-coded, shielded, Industrial Ethernet 100 MBit/s



| Product data                   |                            |
|--------------------------------|----------------------------|
| Item description               | IE-WWASSY4.029-8/S2171     |
| Item-No.                       | 8113225                    |
| Length                         | 8m                         |
| Customs tariff-No.             | 85444290                   |
| Step-File                      | IE-WWASSY4.stp             |
| EAN                            | 4047106312862              |
| Technical data                 |                            |
| Connector                      | male, angled, M12          |
| Number of pins                 | 4                          |
| Pin assignment                 | 1 YE, 2 WH, 3 OG, 4 BU     |
| Coding                         | D                          |
| Rated voltage                  | 60V                        |
| Current load per pin (at 40°C) | 4A                         |
| Insulation resistance          | $\geq 10^9 \Omega$         |
| Resistance                     | $\leq 5 m\Omega$           |
| Transmission features          | Cat5e                      |
| Ambient temperature product    | -30°C...+90°C              |
| Contact material               | Metal, CuSn, gold-plated   |
| Contact-carrier material       | Plastic, TPU, GN           |
| Grip body material             | Plastic, TPU, BK           |
| Coupling nut material          | Metal, CuZn, nickel-plated |
| Shielding                      | with shielding             |
| Standards                      | IEC 61076-2-101            |
| Degree of protection (mounted) | IP65, IP67, IP68           |
| Mechanical life-cycle          | >100 mating cycles         |
| Cable end assembly             | open cable end             |
| Degree of pollution            | 3                          |
| Style                          | angled                     |

## Cable web

## Cat5e, PUR, UL, S2171, PROFINET

Shielded, PUR-cable for industrial applications. The cable is CMX-verified or meets the Cat5e (electrical properties of EN 50288-2-1) requirements. Materials and a constructive setup allow for increased mechanical stresses (abrasion, bending, vibrations etc.) of the cable. A drag-chain application with up to 3 million bending cycles is possible.

|                              |                                                                                                                                                                                                                                                                               |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outer diameter of jacket     | 6.50 mm                                                                                                                                                                                                                                                                       |
| Cable-jacket material        | PUR                                                                                                                                                                                                                                                                           |
| Jacket color                 | GN, similar RAL6018                                                                                                                                                                                                                                                           |
| Wire cross-section           | 1 x 4 x AWG22, star quad                                                                                                                                                                                                                                                      |
| Wire insulation material     | FRNC                                                                                                                                                                                                                                                                          |
| Wire colors                  | WH, BU, OG, YE                                                                                                                                                                                                                                                                |
| Wire structure               | 7 x 0.25 mm                                                                                                                                                                                                                                                                   |
| Bending radius (fixed)       | 4 x Ø-cable                                                                                                                                                                                                                                                                   |
| Bending radius (repeated)    | 8 x Ø-cable                                                                                                                                                                                                                                                                   |
| Temperature range (repeated) | -30°C...+70°C                                                                                                                                                                                                                                                                 |
| Temperature range (fixed)    | -40°C...+75°C                                                                                                                                                                                                                                                                 |
| Drag chain-application       | 3 Mio. bending cycles                                                                                                                                                                                                                                                         |
| Halogen-free                 | Yes                                                                                                                                                                                                                                                                           |
| Transmission features        | Cat5e                                                                                                                                                                                                                                                                         |
| Rated voltage cable          | 600 V UL rating                                                                                                                                                                                                                                                               |
| Special features             | flame retardant, halogen free, high flexibility, hydrolysis proof, LABS free, microbes resistant, oil resistant, ozone resistant, PROFINET Type C, recyclable, RoHs compliant, acid- and alkali resistant, drag chain-adapted, seawater resistant, UN ECE R 118, UV resistant |

## Classification

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27060307 |
| eCl@ss 7.0 | 27060307 |
| eCl@ss 8.0 | 27060307 |
| eCl@ss 9.0 | 27060307 |
| ETIM 5.0   | EC000830 |
| ETIM 6.0   | EC000830 |