



# M8, female, straight, 3 poles, M12, male, straight, 3 poles, sensor-/actuator cable



| Product data                   |                              |                            |
|--------------------------------|------------------------------|----------------------------|
| Item description               | AL-SKP3-1,5-AL-WAS3/S740/S77 |                            |
| Item-No.                       | 8119765                      |                            |
| Length                         | 1.5m                         |                            |
| Customs tariff-No.             | 85444290                     |                            |
| EAN                            | 4047106332723                |                            |
| Technical data                 | A-side                       | B-side                     |
| Connector                      | female, straight, M8         | male, straight, M12        |
| Number of pins                 | 3                            | 3                          |
| Pin assignment                 | 1 BN, 3 BU, 4 BK             | 1 BN, 3 BU, 4 BK           |
| Coding of                      |                              | A                          |
| Rated voltage                  | 60V                          | 250V                       |
| Current load (at 40°C)         | 4A                           | 4A                         |
| Insulation resistance          | ≥10 <sup>9</sup> Ω           | ≥10 <sup>9</sup> Ω         |
| Resistance                     | ≤ 5mΩ                        | ≤ 5mΩ                      |
| Ambient temperature product    | -30°C...+90°C                | -30°C...+90°C              |
| Contact material               | Metal, CuSn, gold-plated     | Metal, CuSn, gold-plated   |
| Contact-carrier material       | Plastic, TPU, BK             | Plastic, TPU, BK           |
| Grip body material             | Plastic, TPU, BK             | Plastic, TPU, BK           |
| Coupling nut material          | Metal, CuZn, nickel-plated   | Metal, CuZn, nickel-plated |
| Sealing (female) material      | FPM/FKM                      |                            |
| Standards                      | IEC 61076-2-104              | IEC 61076-2-101            |
| Degree of protection (mounted) | IP65, IP67, IP68             | IP65, IP67, IP68           |
| Mechanical life-cycle          | >100 mating cycles           | >100 mating cycles         |
| Degree of pollution            | 3                            | 3                          |

## Cable web

PUR, UL, S740, welding sparks resistant, Automotive

Flexible, silicone- and halogen free control cable with high mechanical strength. Due to its outstanding properties in drag-chain adaption, torsionresistance and weld-field immunity, it is very well suited for the flexible applications in robotics, handling- and assembly technology as well as machine tools. The cable meets the UL and CSA (UL10493/20549; cULus) requirements.

|                                |                                                                                                                                                                                                                                                                      |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outer diameter of jacket       | 6.2 mm                                                                                                                                                                                                                                                               |
| Cable-jacket material          | PUR                                                                                                                                                                                                                                                                  |
| Jacket color                   | OG, similar RAL2003                                                                                                                                                                                                                                                  |
| Wire cross-section             | 3 x 0.34 mm <sup>2</sup>                                                                                                                                                                                                                                             |
| Wire insulation material       | PP                                                                                                                                                                                                                                                                   |
| Wire colors                    | BN, BU, BK                                                                                                                                                                                                                                                           |
| Wire structure                 | 42 x 0.10 mm                                                                                                                                                                                                                                                         |
| Bending radius (fixed)         | 5 x Ø-cable                                                                                                                                                                                                                                                          |
| Bending radius (repeated)      | 10 x Ø-cable                                                                                                                                                                                                                                                         |
| Temperature range (repeated)   | -30°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (fixed)      | -40°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (drag chain) | -25°C...+60°C                                                                                                                                                                                                                                                        |
| Drag chain-application         | 5 Mio. cycles                                                                                                                                                                                                                                                        |
| Halogen-free                   | Yes                                                                                                                                                                                                                                                                  |
| Torsion                        | +/-360°/m, ≥ 2 Mio. cycles                                                                                                                                                                                                                                           |
| Rated voltage cable            | ≤300 V                                                                                                                                                                                                                                                               |
| Special features               | flame retardant, halogen free, hydrolysis proof, LABS free, oil resistant, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, drag chain-adapted, welding sparks resistant, seawater resistant, silicone free, torsion resistant, UV resistant |
| Eigenschaften Automotiv        | The cable meets the requirements of MgU-I-B09-41 for sensor-/ actuator cables for the body shop area.                                                                                                                                                                |

## Classification

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27279218 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |
| ETIM 5.0   | EC001855 |
| ETIM 6.0   | EC001855 |

## Accessories

### Mounting-clip, M8

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8047658>

### Mounting-clip, M12

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8047660>

### Torque-wrench set

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431>

### Marking rings Ø 9mm

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=809>

### Screw plug, M8

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8081771>

### Screw cap, M12

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=811>