




# M8, female, angled, 5 poles, M8, male, angled, 5 poles, shielded, sensor-/actuator cable



## Product data

|                    |                               |
|--------------------|-------------------------------|
| Item description   | AL-SWKPS4.5-m-AL-SWSPS4.5/P00 |
| Item-No.           | V0002859                      |
| Länge              | on demand                     |
| Customs tariff-No. | 85444290                      |
| Step-File          | AL-SWKPS4_5_AL-SWSPS4_5.stp   |

| Technical data                 | A-side                       | B-side                       |
|--------------------------------|------------------------------|------------------------------|
| Connector                      | female, angled, M8           | male, angled, M8             |
| Number of pins                 | 5                            | 5                            |
| Pin assignment                 | 1 BN, 2 WH, 3 BU, 4 BK, 5 GY | 1 BN, 2 WH, 3 BU, 4 BK, 5 GY |
| Rated voltage                  | 30V                          | 30V                          |
| Current load (at 40°C)         | 3A                           | 3A                           |
| Insulation resistance          | $\geq 10^9 \Omega$           | $\geq 10^9 \Omega$           |
| Resistance                     | $\leq 5 m\Omega$             | $\leq 5 m\Omega$             |
| Ambient temperature product    | -30°C...+90°C                | -30°C...+90°C                |
| Contact material               | Metal, CuZn, gold-plated     | Metal, CuZn, gold-plated     |
| Contact-carrier material       | Plastic, TPU, BK             | Plastic, TPU, BK             |
| Grip body material             | Plastic, TPU, BK             | Plastic, TPU, BK             |
| Coupling nut material          | Metal, CuZn, nickel-plated   | Metal, CuZn, nickel-plated   |
| Sealing (female) material      | FPM/FKM                      |                              |
| Shielding                      | with shielding               | with shielding               |
| Standards                      | IEC 61076-2-104              | IEC 61076-2-104              |
| Degree of protection (mounted) | IP65, IP67, IP68             | IP65, IP67, IP68             |
| Mechanical life-cycle          | >100 mating cycles           | >100 mating cycles           |
| Degree of pollution            | 3                            | 3                            |

## Cable web PVC, P00, GY

PVC-cable for measurement and control-, and sensor technology. Suitable for applications in dry areas on packaging machines, assembly- and conveyor technology. High flexibility with unstressed movement (conditional drag-chain application possible). Predestined for applications in food- and beverage industry. Very good EMC-features with shielded versions.

|                              |                                                                                                                                                                                     |
|------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outer diameter of jacket     | 5.30 mm                                                                                                                                                                             |
| Cable-jacket material        | PVC                                                                                                                                                                                 |
| Jacket color                 | GY, similar RAL7040                                                                                                                                                                 |
| Wire cross-section           | 5 x 0.25 mm <sup>2</sup>                                                                                                                                                            |
| Wire insulation material     | PVC                                                                                                                                                                                 |
| Wire colors                  | BN, WH, BU, BK, GY                                                                                                                                                                  |
| Wire structure               | 14 x 0.15 mm                                                                                                                                                                        |
| Bending radius (fixed)       | 5 x Ø-cable                                                                                                                                                                         |
| Bending radius (repeated)    | 10 x Ø-cable                                                                                                                                                                        |
| Temperature range (repeated) | 0°C...+80°C                                                                                                                                                                         |
| Temperature range (fixed)    | -25°C...+80°C                                                                                                                                                                       |
| Shielding                    | Yes                                                                                                                                                                                 |
| Rated voltage cable          | ≤300 V                                                                                                                                                                              |
| Special features             | good resistance against oils and chemicals, hydrolysis proof, LABS free, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, sea-water resistant, UV resistant |

## Classification

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27279218 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |
| ETIM 5.0   | EC001855 |
| ETIM 6.0   | EC001855 |

## Accessories

### Mounting-clip, M8

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8047658>

### Torque-wrench set

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431>

### Marking rings Ø 9mm

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=809>

### Screw plug, M8

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8081771>

### Screw cap, M8

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8081761>