


M12, male, straight, 4 poles, grip body with thread, sensor-/actuator cable









Product data			
Item description	AL-WASG4-m/P01		
Item-No.	V0004097		
Länge	on demand		
Customs tariff-No.	85444290		
Step-File	AL-WASG4.stp		
Technical data			
Connector	male, straight, M12, grip body with thread		
Number of pins	4		
Pin assignment	1 BN, 2 WH, 3 BU, 4 BK		
Coding	A		
Rated voltage	250V		
Current load per pin (at 40°C)	4A		
Insulation resistance	>=10 ⁸ Ω		
Resistance	$\leq 5 \text{m}\Omega$		
Ambient temperature product	-30°C+90°C		
Contact material	Metal, CuSn, gold-plated		
Contact-carrier material	Plastic, TPU, BK		
Grip body material	Plastic, TPU, BK		
Coupling nut material	Metal, CuZn, nickel-plated		
Standards	IEC 61076-2-101		
Degree of protection (mounted)	IP65, IP67, IP68		
Mechanical life-cycle	>100 mating cycles		
Cable end assembly	open cable end		
Degree of pollution	3		



Cable web	PVC, UL, P01, GY	
-----------	------------------	--

PVC-cable for measurement and control-, and sensor technology. Suitable for applications in dry areas on packaging machines, assembly- and conveyor technology. High flexibility with unstressed movement (conditional drag-chain application possible). Predestined for applications in food- and beverage industry.

Outer diameter of jacket	4.90 mm		
Cable-jacket material	PVC		
Jacket color	GY, similar RAL7040		
Wire cross-section	4 x 0.34 mm ²		
Wire insulation material	PVC		
Wire colors	BN, WH, BU, BK		
Wire structure	19 x 0.15 mm		
Bending radius (fixed)	5 x Ø-cable		
Bending radius (repeated)	10 x Ø-cable		
Temperature range (repeated)	0°C+80°C		
Temperature range (fixed)	-25°C+80°C		
Rated voltage cable	≤300 V		
Special features	good resistance against oils and chemicals, LABS free, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, seawater resistant, UV resistant		

Classification		
eCl@ss 6.0	27279218	
eCl@ss 7.0	27279218	
eCl@ss 8.0	27279218	
eCl@ss 9.0	27060311	
ETIM 5.0	EC001855	
ETIM 6.0	EC001855	

Α	CC	es	so	rı	es
$\overline{}$	CC	_J	J		•

 $Mounting-set, M12\\ https://www.escha.net/en/products/standard/accessories-for-connectivity/8047664$

 $Torque-wrench\ set\\ https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431$

Marking rings Ø 9mm

scha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=809

Cable Stripping Tool https://www.escha.net/en/products/standard/accessories-for-connectivity/8066215

Cable Stripping Tool https://www.escha.net/en/products/standard/accessories-for-connectivity/8066216

Adapter piece, M12, with protective hose