



M12, female, straight, 4 poles, M12, male, straight, 4 poles, with LED, sensor-/actuator cable



**Product data**

|                    |                           |
|--------------------|---------------------------|
| Item description   | AL-WAK4P2-m-AL-WAS4/S7400 |
| Item-No.           | V0005016                  |
| Length             | on demand                 |
| Customs tariff-No. | 85444290                  |
| Step-File          | AL-WAK4P2_AL-WAS4.stp     |

| Technical data                 | A-side                          | B-side                     |
|--------------------------------|---------------------------------|----------------------------|
| Connector                      | female, straight, M12, with LED | male, straight, M12        |
| Number of pins                 | 4                               | 4                          |
| Pin assignment                 | 1 BN, 2 WH, 3 BU, 4 BK          | 1 BN, 2 WH, 3 BU, 4 BK     |
| Coding of                      | A                               | A                          |
| Rated voltage                  | 30V                             | 250V                       |
| Current load (at 40°C)         | 4A                              | 4A                         |
| Insulation resistance          | $\geq 10^9 \Omega$              | $\geq 10^9 \Omega$         |
| Resistance                     | $\leq 5 m\Omega$                | $\leq 5 m\Omega$           |
| Ambient temperature product    | -30°C...+90°C                   | -30°C...+90°C              |
| Contact material               | Metal, CuSn, gold-plated        | Metal, CuSn, gold-plated   |
| Contact-carrier material       | Plastic, TPU, BK                | Plastic, TPU, BK           |
| Grip body material             | Plastic, TPU, transparent       | Plastic, TPU, BK           |
| Coupling nut material          | Metal, CuZn, nickel-plated      | Metal, CuZn, nickel-plated |
| Circuit logic                  | pnp                             |                            |
| Signal status-indicator        | LED YE                          |                            |
| Operating voltage-indicator    | LED GN                          |                            |
| Sealing (female) material      | FPM/FKM                         |                            |
| Standards                      | IEC 61076-2-101                 | IEC 61076-2-101            |
| Degree of protection (mounted) | IP65, IP67, IP68                | IP65, IP67, IP68           |
| Mechanical life-cycle          | >100 mating cycles              | >100 mating cycles         |
| Degree of pollution            | 3                               | 3                          |

## Cable web

PUR, UL, S7400, robotic

Flexible, silicone- and halogen free control cable with high mechanical strength. Due to its outstanding properties in drag-chain adaption, torsionresistance and weld-field immunity, it is very well suited for the flexible applications in robotics, handling- and assembly technology as well as machine tools. The cable meets the UL and CSA (UL10493/20549; cULus) requirements.

|                                |                                                                                                                                                                                                                                                                      |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outer diameter of jacket       | 5.20 mm                                                                                                                                                                                                                                                              |
| Cable-jacket material          | PUR                                                                                                                                                                                                                                                                  |
| Jacket color                   | OG, similar RAL2003                                                                                                                                                                                                                                                  |
| Wire cross-section             | 4 x 0.34 mm <sup>2</sup>                                                                                                                                                                                                                                             |
| Wire insulation material       | PP                                                                                                                                                                                                                                                                   |
| Wire colors                    | BN, WH, BU, BK                                                                                                                                                                                                                                                       |
| Wire structure                 | 42 x 0.10 mm                                                                                                                                                                                                                                                         |
| Bending radius (fixed)         | 5 x Ø-cable                                                                                                                                                                                                                                                          |
| Bending radius (repeated)      | 10 x Ø-cable                                                                                                                                                                                                                                                         |
| Temperature range (repeated)   | -30°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (fixed)      | -40°C...+90°C                                                                                                                                                                                                                                                        |
| Temperature range (drag chain) | -25°C...+60°C                                                                                                                                                                                                                                                        |
| Drag chain-application         | ≥ 10 Mio. cycles                                                                                                                                                                                                                                                     |
| Halogen-free                   | Yes                                                                                                                                                                                                                                                                  |
| Torsion                        | +/-360°/m, ≥ 10 Mio. cycles                                                                                                                                                                                                                                          |
| Rated voltage cable            | ≤300 V                                                                                                                                                                                                                                                               |
| Special features               | flame retardant, halogen free, hydrolysis proof, LABS free, oil resistant, ozone resistant, recyclable, RoHs compliant, acid- and alkali resistant, drag chain-adapted, welding sparks resistant, seawater resistant, silicone free, torsion resistant, UV resistant |

## Classification

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27279218 |
| eCl@ss 7.0 | 27279218 |
| eCl@ss 8.0 | 27279218 |
| eCl@ss 9.0 | 27060311 |
| ETIM 5.0   | EC001855 |
| ETIM 6.0   | EC001855 |

## Accessories

### Mounting-clip, M12

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8047660>

### Torque-wrench set

<https://www.escha.net/en/products/standard/accessories-for-connectivity/8055431>

### Marking rings Ø 9mm

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=809>

### Screw plug, M12

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=812>

### Screw cap, M12

<https://www.escha.net/en/products/standard/accessories-for-connectivity?p=1&o=3&n=15&f=811>